ISSUE	DATE	CHG	DLR	INITS	REVISION
A	7-1-44				REVISED
B	8-18-44				REVISED
C	10-2-44				REVISED
D	10-5-44				REVISED
E	2-1-45				REVISED
F	4-3-45				REVISED
G	4-10-45				REVISED
H	4-13-45				REVISED
J	4-17-45				REVISED
K	10-2-45				REVISED
L	12-1-45				REVISED
M	1-8-46				REVISED
P	1-15-46				REVISED
Q	1-29-46				REVISED
R	2-5-46				REVISED
S	2-8-46				REVISED
T	2-14-46				REVISED
U	2-26-46				REVISED
V	3-12-46				REVISED
W	3-25-46				REVISED

ALL DRILLED HOLES 3/8" DIA AND OVER ARE TO BE SPOT FACED FOR BEARING SURFACE ONLY BY 3/8" DEEP, UNLESS OTHERWISE NOTED. DIA OF SPOT = DIA OF HOLE + 1/8" (1/8" MIN. DIA OF SPOT MAKES 1/8" MIN. DIA OF HOLE)

NOTE:
EXCEPT AS OTHERWISE NOTED -
ALLOW FOR FINISH ON ALL DISCARDED FORGED FIN.
ALL ROUGH FINISHING TO BE DONE BY G.S.C. CORP.
ALL BOLTON RIVET HOLES TO BE DRILLED & UNDER NOMINAL DIA. BY 1/16" & CORED AND REAMED TO SIZE BY LOCO BLDR.
ALL HOLES DESIGNATED AS DRILL TO BE DRILLED TO SIZE SHOWN BY G.S.C. CORP.
ALL DRILLING FOR TAPPED HOLES TO BE DONE BY G.S.C. CORP.
ALL TAPPING TO BE DONE BY LOCO BLDR.
ALL CORNERS TO BE ROUNDED WITH NOT LESS THAN 1/8" RADIUS
ALL FILLETS TO BE 1/8" RADIUS

B-52970

EDITOR'S SETTING: XXXX